



Einbauempfehlung und Abmaße bei Verwendung der Spannschraube
DIN 787 (mit Stützverlängerung 6312S)

B1	D x LS	Abmessung DIN 787	Spannbereich
13	M10 x 39	M10 x 10 x 100	18 - 31
13	M10 x 39	M12 x 12 x 160	18 - 95
13	M10 x 39	M12 x 14 x 160	18 - 95
17	M12 x 49	M12 x 12 x 200	26 - 123
17	M12 x 49	M12 x 14 x 200	26 - 123
17	M12 x 49	M16 x 16 x 200	26 - 123
17	M12 x 49	M16 x 18 x 200	26 - 123
17	M12 x 94	M12 x 12 x 200	26 - 120
17	M12 x 94	M12 x 14 x 200	26 - 120
17	M12 x 94	M16 x 16 x 250	26 - 166
17	M12 x 94	M16 x 18 x 250	26 - 166
21	M16 x 55	M16 x 16 x 250	33 - 141
21	M16 x 55	M16 x 18 x 250	33 - 141
21	M16 x 55	M20 x 20 x 250	33 - 141
21	M16 x 55	M20 x 22 x 250	33 - 141
21	M16 x 90	M16 x 16 x 250	33 - 150
21	M16 x 90	M16 x 18 x 250	33 - 150
21	M16 x 90	M20 x 20 x 315	33 - 173
21	M16 x 90	M20 x 22 x 315	33 - 173
25	M20 x 69	M20 x 20 x 315	41 x 177
25	M20 x 69	M20 x 22 x 315	41 x 177
25	M20 x 69	M24 x 24 x 315	41 x 177
25	M20 x 69	M24 x 28 x 315	41 x 177
25	M20 x 109	M20 x 20 x 315	41 - 197